

Catalog No. SOB **120 - 140 - 150** **d** **120 - 140 - 150** **L**

d	F7	D	m6	R	g	Applicable washer	Catalog No.	d	D	L
100		120	+0.035 +0.013	2	2	SOBW100		100	120	40 50 60 70 80 90 100 120 140
110	+0.071 +0.036	130				—		110	130	70 80 100 120
120		140		3	3	SOBW120	SOB	120	140	80 90 100 120
125		145	+0.040 +0.015					125	145	140 150
130		150						130	150	100 130
140	+0.083 +0.043	160				—		140	160	100 140
150		170			4			150	170	80 100 150
160		180			3			160	180	80 100 150

SOBW

Sliding direction



SOBWN

Sliding direction



SOBWN (Type Without Bolt Holes)

Sliding direction



Material : Bronze with Graphite (SO#50 SP2)



Catalog No. SOBWN **10**

d(Actual size)	D	T	P.C.D	Bolt mounting hole Quantity (Flat head screw)	d1	Catalog No.	d(nominal)
10.2	30		20				10
12.2							12
13.2	40		28				13
14.2		3		M3	3.5		14
15.2							15
16.2	50		35	2			16
18.2							18
20.2							20
25.2	55	5	40				25
30.2	60		45	M5	6		30
35.2	70		50				35
40.2	80	7	60			SOBWN	40
45.3	90		67.5				45
50.3	100		75	M6	7		50
55.3	110	8	85				55
60.3	120		90				60
65.3	125		95				65
70.3	130		100				70
75.3	140		110	M8	9		75
80.3	150	10	120				80
90.5	170		140				90
100.5	190		160	M10	11		100
120.5	200		175				120

■ Type without Bolt hole

d(Actual size)	D	T	Catalog No.	d(nominal)
10.2	30			10
12.2	40	3		12
16.2	50		SOBWN	16
20.2				20
25.2	55	5		25



Order

Catalog No. SOBWN **10**